

## INDUSTRIAL COMPONENT DATA

# 8WA1011-3DH21 SIEMENS Through-type terminal thermoplast Screw terminal on both sides Terminal block 3-pole, ..

Brand: SIEMENS | Manufacturer Part Number: 8WA1011-3DH21



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | SIEMENS                     |
| MPN / Reference | 8WA1011-3DH21               |
| Catalog number  | 10113                       |
| Category        | Feed-through terminal block |
| Minimum order   | 20 Pcs                      |
| Document ID     | EO-0BF67AA3B0               |
| Generated       | 2026-08-05                  |

## Product Overview

Through-type terminal thermoplast Screw terminal on both sides Terminal block 3-pole, beige 24.5mm, Sz. 6  
Passage terminal, insulating thermal material, screw connection on both sides, 3-pole terminal block, beige 24.5mm, size 6  
(\*\* ATTENTION: Price per 1 Unit and Minimum Quantity / Order Multiple 20 Units \*\*). Manufactured to customer specifications. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

## Technical data

Through-type terminal thermoplast Screw terminal on both sides Terminal block 3-pole, beige 24.5mm, Sz. 6

## Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

## General technical data

terminal contact spacing 25 mm

operating voltage / rated value 800 V

## Protection class

combustibility class according to UL 94 V2

## Main circuit

operational current / rated value 41 A

Appearance

color beige

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 11 mm

connectable conductor cross-section / solid

? minimum 6 mm<sup>2</sup>

? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 6 mm<sup>2</sup>

? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 6 mm<sup>2</sup>

? with core end processing / maximum 6 mm<sup>2</sup>

? without core end processing / minimum 6 mm<sup>2</sup>

? without core end processing / maximum 6 mm<sup>2</sup>

tightening torque / with screw-type terminals

? minimum 0.8 N·m

? maximum 1 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 26 mm

length 41 mm

fastening method DIN rail 35 mm

net weight 38 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maxim...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA1011-3DH21 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.