

INDUSTRIAL COMPONENT DATA

8WA1206 SIEMENS Through-type terminal thermoplast Screw terminal on both sides Single terminal 25 mm, Sz. 70

Brand: SIEMENS | Manufacturer Part Number: 8WA1206



Manufacturer	SIEMENS
MPN / Reference	8WA1206
Catalog number	10000
Category	Feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-4D758EE12F
Generated	2026-08-02

Product Overview

Through-type terminal thermoplast Screw terminal on both sides Single terminal 25 mm, Sz. 70
Passage terminal, insulating thermal material, screw connection on both sides, individual terminal 25mm, size 70 (**
ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 10 Units **). Manufactured to customer
specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

Additional Product Information

Technical data

Through-type terminal thermoplast Screw terminal on both sides Single terminal 25 mm, Sz. 70

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 25 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V2

Main circuit

operational current / rated value 192 A

Appearance

color beige

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 25 mm

connectable conductor cross-section / solid

? minimum 10 mm²

? maximum 95 mm²

connectable conductor cross-section / stranded

? minimum 16 mm²

? maximum 95 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 16 mm²

? with core end processing / maximum 70 mm²

? without core end processing / minimum 16 mm²

? without core end processing / maximum 95 mm²

tightening torque / with screw-type terminals

? minimum 6 N·m

? maximum 6 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 26 mm

length 74 mm

fastening method DIN rail 35 mm

net weight 170 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA1206 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.