

INDUSTRIAL COMPONENT DATA

8WA1304 SIEMENS Through-type terminal thermoplast Screw terminal on both sides Block 3 terminals 30.2 mm, Si..

Brand: SIEMENS | Manufacturer Part Number: 8WA1304



Manufacturer	SIEMENS
MPN / Reference	8WA1304
Catalog number	10000
Category	Feed-through terminal block
Minimum order	20 Pcs
Document ID	EO-B3BB3C3D00
Generated	2026-08-03

Product Overview

Through-type terminal thermoplast Screw terminal on both sides Block 3 terminals 30.2 mm, Size 16
Passage terminal, insulating thermal material, screw connection on both sides, block 3 terminals 30.2mm, size 16 (**
ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 20 Units **). Manufactured to customer
specifications. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

Additional Product Information

Technical data

Through-type terminal thermoplast Screw terminal on both sides Block 3 terminals 30.2 mm, Size 16

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 10 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V2

Main circuit

operational current / rated value 76 A

Appearance

color beige

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 13 mm

connectable conductor cross-section / solid

? minimum 1.5 mm²

? maximum 16 mm²

connectable conductor cross-section / stranded

? minimum 2.5 mm²

? maximum 16 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 1 mm²

? with core end processing / maximum 16 mm²

? without core end processing / minimum 2.5 mm²

? without core end processing / maximum 16 mm²

tightening torque / with screw-type terminals

? minimum 1.2 N·m

? maximum 1 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 26 mm

length 41 mm

fastening method DIN rail 35 mm

net weight 66 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? max...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA1304 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.