

INDUSTRIAL COMPONENT DATA

8WA2011-3KE31 SIEMENS actuator terminals (L-, S, A) without LED, PNP spring-l. term., sz 1.5mm2, 5mm

Brand: SIEMENS | Manufacturer Part Number: 8WA2011-3KE31



Manufacturer	SIEMENS
MPN / Reference	8WA2011-3KE31
Catalog number	20113
Category	Sensor/actuator terminal block
Minimum order	20 Pcs
Document ID	EO-1D91B8A6B2
Generated	2026-08-05

Product Overview

actuator terminals (L-, S, A) without LED, PNP spring-l. term., sz 1.5mm2, 5mm

Borne actor (L-,S,A), without led, PNP, encapsulated traction spring, size 1, 5mm2, 5mm (** ATTENTION : Price per 1 Unit and Minimum Quantity / Multiplo of Order 20 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

actuator terminals (L-, S, A) without LED, PNP spring-l. term., sz 1.5mm2, 5mm

Model

product brand name ALPHA

product designation Actuator terminals

design of LED initiator/actuator terminal No

design of terminal / terminal levels internally linked No

General technical data

insulation material thermoplastic

terminal contact spacing 5 mm

operating voltage / rated value 64 V

Protection class

combustibility class according to UL 94 V2

Main circuit

operational current / rated value 10 A

Appearance

color grey

? of the light source without

Product details

product function / infeed function No

product component

? required / end cover plate No

? PE connection No

? shield connection No

? disconnecter No

product feature / cross-connectable No

Number

number of terminal levels 4

number of terminal points / per terminal level 1

Connections

connectable conductor cross-section / solid

? minimum 1.5 mm²? maximum 1.5 mm²

connectable conductor cross-section / stranded

? minimum 1.5 mm²? maximum 1.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 1.5 mm²? with core end processing / maximum 1.5 mm²? without core end processing / minimum 1.5 mm²? without core end processing / maximum 1.5 mm²**type of connection**

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

fastening method DIN rail 35 mm

net weight 11 g

material / of the insulating body Thermoplast

Downloads and manuals

Gene...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA2011-3KE31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.