

INDUSTRIAL COMPONENT DATA

8WA2111-3KE13 SIEMENS initiator terminals (L+, L-, shield, A) with yellow LED, PNP, 15-30V, spring-I. term.,...

Brand: SIEMENS | Manufacturer Part Number: 8WA2111-3KE13



Manufacturer	SIEMENS
MPN / Reference	8WA2111-3KE13
Catalog number	1000
Category	Sensor/actuator terminal block
Minimum order	1000 Pcs
Document ID	EO-142DC5AC69
Generated	2026-08-06

Product Overview

initiator terminals (L+, L-, shield, A) with yellow LED, PNP, 15-30V, spring-I. term., sz 1.5mm2, 5mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

ETIM: EC000900 - Sensor/actuator terminal block

Value Unit

Inflammability class of insulation material according to with UL94 (EF002521) -

Connection position (EF008219) -

Rated voltage (EF000228) - V

Number of levels (EF002659) -

Number of clamp positions per level (EF002660) -

Internally connected stages (EF002661) -

Type of electrical connection 1 (EF002526) Other

Type of electrical connection 2 (EF002527) Other

Mounting method (EF000003) Other

Cross connectable (EF005717) -

Material insulation body (EF007543) Other

Operating temperature (EF002393) ['- ', '-'] °C

Explosion-tested version 'Ex e' (EF008498) -

Closing plate required (EF002525) -
Colour (EF000007) Other
Colour lamp (EF001402) Other
LED switching for (EF002537) No
With PE connection (EF002534) -
With shield connection (EF002535) -
With power supply function (EF002536) -
Disconnect function (EF006183) -
Length (EF001438) - mm
Connectable conductor cross section solid-core (EF007337) - mm²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339) - mm²
Connectable conductor cross section fine-strand without cable end sleeve (EF007341) - mm²
Rated current I_n (EF008250) - A
Connectable conductor cross section multi-wired (EF007343) - mm²
Width/grid dimension (EF002522) - mm
Height at lowest possible mounting height (EF002523) - mm
initiator terminals (L+, L-, shield, A) with yellow LED, PNP, 15-30V, spring-l. term., sz 1.5mm², 5mm
Model
product brand name ALPHA
Product designation Initiator t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WA2111-3KE13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.