

INDUSTRIAL COMPONENT DATA

8WH1000-0AH02 SIEMENS Terminal block, 6 mm² red Screw mounting 2 connections Red

Brand: SIEMENS | Manufacturer Part Number: 8WH1000-0AH02



Manufacturer	SIEMENS
MPN / Reference	8WH1000-0AH02
Catalog number	10000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-092D7CB74E
Generated	2026-08-04

Product Overview

Terminal block, 6 mm² red Screw mounting 2 connections Red

RAIL TERMINAL ,6MM² RED SCREW FIXATION 2 NETWORK CONNECTIONS (** ATTENTION : Price per 1 Unit and Minimum Quantity / Multiplo order 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Terminal block, 6 mm² red Screw mounting 2 connections Red

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 8 mm

operating voltage / rated value 1 000 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 41 A

Appearance

color red

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 0.2 mm²? maximum 10 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.2 mm²? with core end processing / maximum 6 mm²

tightening torque / with screw-type terminals

? minimum 1.5 N·m

? maximum 2 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 47.5 mm

length 48 mm

fastening method DIN rail 35 mm

net weight 15 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.co...>

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH1000-0AH02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.