

INDUSTRIAL COMPONENT DATA

8WH1000-0CK07 SIEMENS Through-type PE terminal with screw terminal Terminal width 12.0 mm Color green-yellow..

Brand: SIEMENS | Manufacturer Part Number: 8WH1000-0CK07



Manufacturer	SIEMENS
MPN / Reference	8WH1000-0CK07
Catalog number	10000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-8D3EF7D2B4
Generated	2026-08-02

Product Overview

Through-type PE terminal with screw terminal Terminal width 12.0 mm Color green-yellow Cross-section: 16 mm²
PE PITCH TERMINAL WITH SCREW CONNECTION WIDE TERMINAL 12.0 MM GREEN-YELLOW SECTION: 16 MM² (**
ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited.
Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Through-type PE terminal with screw terminal Terminal width 12.0 mm Color green-yellow Cross-section: 16 mm²

Model

product brand name SENTRON

General technical data

terminal contact spacing 12 mm

Protection class

combustibility class according to UL 94 V0

Appearance

color green-yellow

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 14 mm

connectable conductor cross-section / solid

? minimum 1.5 mm²? maximum 25 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 1.5 mm²? with core end processing / maximum 16 mm²

tightening torque / with screw-type terminals

? minimum 2.5 N·m

? maximum 3 N·m

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 55 mm

length 55 mm

fastening method DIN rail 35 mm

net weight 47 g

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH1000-0...>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 8WH1000-0CK07 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.