

INDUSTRIAL COMPONENT DATA

8WH1000-1PH38 SIEMENS Fuse terminal LED 10-30 V with screw terminal Terminal size 6.0 mm² Terminal width 8.2..

Brand: SIEMENS | Manufacturer Part Number: 8WH1000-1PH38



Manufacturer	SIEMENS
MPN / Reference	8WH1000-1PH38
Catalog number	10001
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-62CB66D2C5
Generated	2026-08-05

Product Overview

Fuse terminal LED 10-30 V with screw terminal Terminal size 6.0 mm² Terminal width 8.2 mm Color black Fuse 6.3x 32 mm

LED SAFETY TERMINAL 10-30V WITH SCREW CONNECTION SIZE TERMINAL 6.0 MM² TERMINAL WIDTH 8.2 MM BLACK FUSE 6.3 X 32 MM (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **).
Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Fuse terminal LED 10-30 V with screw terminal Terminal size 6.0 mm² Terminal width 8.2 mm Color black Fuse 6.3x 32 mm

Model

product brand name SENTRON

General technical data

terminal contact spacing 8 mm

Supply voltage

operating voltage / rated value 630 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 10 A

Appearance

color black

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

Connections

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 0.2 mm²? maximum 10 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.2 mm²? with core end processing / maximum 6 mm²

type of connection

? 1 screw-type terminal

? 2 screw-type terminal

position / of the terminal lateral

Mechanical Design

height / with lowest-profile installation 73 mm

length 58 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH1000-1PH38>

Service&Support (Manuals, Certificates...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH1000-1PH38 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.