

INDUSTRIAL COMPONENT DATA

8WH1000-6KG00 SIEMENS Diode isolating terminal with screw terminal Terminal size 4.0 mm2 Terminal width 6.2 ..

Brand: SIEMENS | Manufacturer Part Number: 8WH1000-6KG00



Manufacturer	SIEMENS
MPN / Reference	8WH1000-6KG00
Catalog number	10006
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-6EF141DD3C
Generated	2026-08-03

Product Overview

Diode isolating terminal with screw terminal Terminal size 4.0 mm2 Terminal width 6.2 mm Color gray Passage from right to left

DIODE SEPARATION TERMINAL WITH SCREW CONNECTION SIZE BORNE 4.0 MM2 WIDTH OF BORNE 6.2 MM GRAY COLOR STEP FROM RIGHT TO LEFT (** ATTENTION : Price per 1 Unit and Minimum Quantity / Multiplo of Order 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

Additional Product Information

Technical data

Diode isolating terminal with screw terminal Terminal size 4.0 mm2 Terminal width 6.2 mm Color gray Passage from right to left

Model

product brand name SENTRON

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 6 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 1 A

Appearance

color grey

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 9 mm

connectable conductor cross-section / solid

? maximum 6 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.1 mm²? with core end processing / maximum 4 mm²

tightening torque / with screw-type terminals

? minimum 0.6 N·m

? maximum 1 N·m

Mechanical Design

height / with lowest-profile installation 47.5 mm

length 48 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/produ...>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 8WH1000-6KG00 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.