


INDUSTRIAL COMPONENT DATA

8WH1020-5FF00 SIEMENS Two-tier diode terminal with screw terminal Terminal size 2.5 mm² Terminal width 5.2 mm..

Brand: SIEMENS | Manufacturer Part Number: 8WH1020-5FF00



Manufacturer	SIEMENS
MPN / Reference	8WH1020-5FF00
Catalog number	10205
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F36DC6BD5D
Generated	2026-08-05

Product Overview

Two-tier diode terminal with screw terminal Terminal size 2.5 mm² Terminal width 5.2 mm Color gray with diodes Passage from top to bottom L and bottom R to bottom L

TWO-STORY DIODE TERMINAL WITH SCREW CONNECTION SIZE TERMINAL 2.5 MM² TERMINAL WIDTH 5.2 MM GRAY COLOR WITH ARR-AB LEFT STEP DIODES AND AB DER-AB IZQ (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Two-tier diode terminal with screw terminal Terminal size 2.5 mm² Terminal width 5.2 mm Color gray with diodes Passage from top to bottom L and bottom R to bottom L

Model

product brand name SENTRON

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 5 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 24 A

Appearance

color grey

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 2

number of terminal points / per terminal level 2

Connections

stripped length 9 mm

connectable conductor cross-section / solid

? maximum 4 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.1 mm²? with core end processing / maximum 3 mm²

tightening torque / with screw-type terminals

? minimum 0.6 N·m

? maximum 1 N·m

Mechanical Design

height / with lowest-profile installation 65 mm

length 70 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry...>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 8WH1020-5FF00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.