


INDUSTRIAL COMPONENT DATA

8WH1020-5JF30 SIEMENS Two-tier terminals with LED 24 V DC, 2.5 mm2 Screw mounting gray with LED 24 V DC, 2.5..

Brand: SIEMENS | Manufacturer Part Number: 8WH1020-5JF30



Manufacturer	SIEMENS
MPN / Reference	8WH1020-5JF30
Catalog number	10205
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-A35BAF767B
Generated	2026-08-05

Product Overview

Two-tier terminals with LED 24 V DC, 2.5 mm2 Screw mounting gray with LED 24 V DC, 2.5 mm2
 TERMINAL OF 2 FLOORS WITH LED 24VDC, 2,5MM2 FIXING BY GRAY SCREW WITH LED 24VDC, 2,5MM2 (**
 ATTENTION: Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancellations and returns limited.
 Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

Additional Product Information

Technical data

Two-tier terminals with LED 24 V DC, 2.5 mm2 Screw mounting gray with LED 24 V DC, 2.5 mm2

Model

product brand name SENTRON

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 3 mm

operating voltage / rated value 24 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 24 A

Appearance

color grey

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 2

number of terminal points / per terminal level 2

Connections

stripped length 9 mm

connectable conductor cross-section / solid

? maximum 4 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.1 mm²? with core end processing / maximum 4 mm²

tightening torque / with screw-type terminals

? minimum 0.6 N·m

? maximum 1 N·m

Mechanical Design

height / with lowest-profile installation 65 mm

length 70 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH1020-5JF30>

Service&Support...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend SIEMENS / 8WH1020-5JF30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.