

## INDUSTRIAL COMPONENT DATA

# 8WH2000-0AE00 SIEMENS Through-type terminals with spring-loaded connection, Cross-section: 0.14-1.5 mm<sup>2</sup>, Wid..

Brand: SIEMENS | Manufacturer Part Number: 8WH2000-0AE00



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | SIEMENS                     |
| MPN / Reference | 8WH2000-0AE00               |
| Catalog number  | 20000                       |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-B1DBC7C53A               |
| Generated       | 2026-08-02                  |

## Product Overview

Through-type terminals with spring-loaded connection, Cross-section: 0.14-1.5 mm<sup>2</sup>, Width: 4.2mm, Color: gray  
Spring connection passage terminal, section: 0.14 - 1.5 mm<sup>2</sup>, width: 4.2 mm, color: grey ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancellations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

## Technical data

Through-type terminals with spring-loaded connection, Cross-section: 0.14-1.5 mm<sup>2</sup>, Width: 4.2mm, Color: gray

## Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

## General technical data

terminal contact spacing 4 mm

operating voltage / rated value 500 V

## Protection class

combustibility class according to UL 94 V0

## Main circuit

operational current / rated value 18 A

**Appearance**

color grey

**Product details**

product component / required / end cover plate No

**Number**

number of terminal levels 1

number of terminal points / per terminal level 2

**Connections**

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 1.5 mm<sup>2</sup>? maximum 1.5 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 1.5 mm<sup>2</sup>? maximum 1.5 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 1.5 mm<sup>2</sup>? with core end processing / maximum 2 mm<sup>2</sup>? without core end processing / minimum 1.5 mm<sup>2</sup>? without core end processing / maximum 1.5 mm<sup>2</sup>

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

**Mechanical Design**

fastening method DIN rail 35 mm

net weight 5 g

material / of the insulating body Other

**Environmental conditions**

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation****Miscellaneous**

Further informat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2000-0AE00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.