

INDUSTRIAL COMPONENT DATA

8WH2000-0AK00 SIEMENS Through-type terminals with spring-loaded connection, Cross-section: 1.5-16 mm², Width..

Brand: SIEMENS | Manufacturer Part Number: 8WH2000-0AK00



Manufacturer	SIEMENS
MPN / Reference	8WH2000-0AK00
Catalog number	20000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-3DF8DE46B2
Generated	2026-08-04

Product Overview

Through-type terminals with spring-loaded connection, Cross-section: 1.5-16 mm², Width: 12mm, Color: gray
Spring connection passage terminal, section: 1.5 - 16 mm², width: 12 mm, color: grey (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Through-type terminals with spring-loaded connection, Cross-section: 1.5-16 mm², Width: 12mm, Color: gray

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 12 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 90 A

Appearance

color grey

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 18 mm

connectable conductor cross-section / solid

? minimum 25 mm²? maximum 25 mm²

connectable conductor cross-section / stranded

? minimum 25 mm²? maximum 25 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 16 mm²? with core end processing / maximum 16 mm²? without core end processing / minimum 16 mm²? without core end processing / maximum 16 mm²

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

fastening method DIN rail 35 mm

net weight 37 g

material / of the insulating body Other

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**

Inf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2000-0AK00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.