

## INDUSTRIAL COMPONENT DATA

# 8WH2000-0CJ07 SIEMENS Protective conductor terminal with spring-loaded connection, Cross-section: 1.5-10 mm2..

Brand: SIEMENS | Manufacturer Part Number: 8WH2000-0CJ07



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | SIEMENS               |
| MPN / Reference | 8WH2000-0CJ07         |
| Catalog number  | 20000                 |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-0FD738F9           |
| Generated       | 2026-08-04            |

## Product Overview

Protective conductor terminal with spring-loaded connection, Cross-section: 1.5-10 mm<sup>2</sup>, Width: 10mm, Color: green-yellow  
Spring connection earth terminal, section: 1.5 - 10 mm<sup>2</sup>, width: 10mm, color: green-yellow ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancellations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

## Technical data

Protective conductor terminal with spring-loaded connection, Cross-section: 1.5-10 mm<sup>2</sup>, Width: 10mm, Color: green-yellow

## Model

product brand name ALPHA

product designation PE through-type terminal

## General technical data

insulation material thermoplastic

terminal contact spacing 10.2 mm

## Protection class

combustibility class according to UL 94 V0

## Appearance

color green-yellow

## Product details

product feature / PEN function Yes

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 18 mm

connectable conductor cross-section / solid

? minimum 1.5 mm<sup>2</sup>

? maximum 16 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 1.5 mm<sup>2</sup>

? maximum 16 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 1.5 mm<sup>2</sup>

? with core end processing / maximum 10 mm<sup>2</sup>

? without core end processing / minimum 1.5 mm<sup>2</sup>

? without core end processing / maximum 10 mm<sup>2</sup>

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 50.5 mm

length 71.5 mm

fastening method DIN rail 35 mm

net weight 34 g

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 35 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Fur...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2000-0CJ07 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.