

INDUSTRIAL COMPONENT DATA

8WH2000-1BG38 SIEMENS Fuse terminal with illuminated indicator, 24 V DC with 4 mm2 spring-loaded connection,..

Brand: SIEMENS | Manufacturer Part Number: 8WH2000-1BG38



Manufacturer	SIEMENS
MPN / Reference	8WH2000-1BG38
Catalog number	20001
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-28F319BBD2
Generated	2026-08-03

Product Overview

Fuse terminal with illuminated indicator, 24 V DC with 4 mm2 spring-loaded connection, for automatic circuit breakers, Width: 8.2mm, Color: black only for short-circuit

Fuse terminal with led, 24v dc for 4 mm2 spring connection cable, width: 8.2 mm, color: black (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Fuse terminal with illuminated indicator, 24 V DC with 4 mm2 spring-loaded connection, for automatic circuit breakers, Width: 8.2mm, Color: black only for short-circuit

Model

product brand name ALPHA

type of light source / as defect indicator LED

design of the fuse link blade-type fuse

design of fuse holder pluggable

General technical data

insulation material others

terminal contact spacing 8.2 mm

Supply voltage

operating voltage / rated value 400 V
type of voltage / for supply of the defect indicator others
Protection class
combustibility class according to UL 94 V0
Main circuit
operational current / rated value 30 A
Appearance
color black
Product details
product component / required / end cover plate No
Number
number of terminal levels 1
Connections
stripped length 12 mm
connectable conductor cross-section / solid
? minimum 6 mm²
? maximum 6 mm²
connectable conductor cross-section / stranded
? minimum 6 mm²
? maximum 6 mm²
connectable conductor cross-section / finely stranded
? with core end processing / minimum 4 mm²
? with core end processing / maximum 4 mm²
? without core end processing / minimum 4 mm²
? without core end processing / maximum 4 mm²
type of connection
? 1 spring-loaded terminal
? 2 spring-loaded terminal
position / of the terminal top
Mechanical Design
height / with lowest-profile installation 43.5 mm
length 86.5 mm
fastening method DIN rail 35 mm
material / of the insulating body Other
Downloads and manuals
General Product Approval Declara...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2000-1BG38 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.