

INDUSTRIAL COMPONENT DATA

8WH2000-1HG08 SIEMENS Fuse terminal for G fuse links 6x 32 mm, with 4 mm2 spring-loaded connection, Width: 8..

Brand: SIEMENS | Manufacturer Part Number: 8WH2000-1HG08



Manufacturer	SIEMENS
MPN / Reference	8WH2000-1HG08
Catalog number	20001
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-22520BC6C2
Generated	2026-08-05

Product Overview

Fuse terminal for G fuse links 6x 32 mm, with 4 mm2 spring-loaded connection, Width: 8.2mm, Color: black
 Fuse terminal for fuses type g of 6x32 mm, for cable of 4mm2 of connection per spring, width: 8.2 mm, color: black (**
 ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited.
 Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

Additional Product Information

Technical data

Fuse terminal for G fuse links 6x 32 mm, with 4 mm2 spring-loaded connection, Width: 8.2mm, Color: black

Model

product brand name ALPHA

type of light source / as defect indicator without

design of the fuse link glass fuse 6.3x32 mm

design of fuse holder pluggable

General technical data

insulation material others

terminal contact spacing 8.2 mm

Supply voltage

operating voltage / rated value 400 V

type of voltage / for supply of the defect indicator others

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 10 A

Appearance

color black

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

Connections

stripped length 12 mm

connectable conductor cross-section / solid

? minimum 6 mm²

? maximum 6 mm²

connectable conductor cross-section / stranded

? minimum 6 mm²

? maximum 6 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 4 mm²

? with core end processing / maximum 4 mm²

? without core end processing / minimum 4 mm²

? without core end processing / maximum 4 mm²

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 69 mm

length 76.5 mm

fastening method DIN rail 35 mm

material / of the insulating body Other

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Furth...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2000-1HG08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.