


**INDUSTRIAL COMPONENT DATA**

# 8WH2004-0AF00 SIEMENS Through-type terminals with spring-loaded connection, 4 terminals Cross-section: 0.08-..

Brand: SIEMENS | Manufacturer Part Number: 8WH2004-0AF00



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | SIEMENS                     |
| MPN / Reference | 8WH2004-0AF00               |
| Catalog number  | 20040                       |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-479B2AB36F               |
| Generated       | 2026-08-01                  |

## Product Overview

Through-type terminals with spring-loaded connection, 4 terminals Cross-section: 0.08-2.5 mm<sup>2</sup>, Width: 5.2mm, Color: gray  
Spring connection passage terminal, 4 connection points section: 0.08 - 2.5 mm<sup>2</sup>, width: 5.2 mm, color: gray ( \*\*  
ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancelations and returns limited.  
Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

Through-type terminals with spring-loaded connection, 4 terminals Cross-section: 0.08-2.5 mm<sup>2</sup>, Width: 5.2mm, Color: gray  
Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

**General technical data**

terminal contact spacing 5 mm

operating voltage / rated value 800 V

**Protection class**

combustibility class according to UL 94 V0

**Main circuit**

operational current / rated value 28 A

Appearance

color grey

Product details

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 4

Connections

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 4 mm<sup>2</sup>

? maximum 4 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 4 mm<sup>2</sup>

? maximum 4 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 2.5 mm<sup>2</sup>

? with core end processing / maximum 3 mm<sup>2</sup>

? without core end processing / minimum 2.5 mm<sup>2</sup>

? without core end processing / maximum 2.5 mm<sup>2</sup>

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

fastening method DIN rail 35 mm

net weight 10 g

material / of the insulating body Other

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further inf...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2004-0AF00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.