

**INDUSTRIAL COMPONENT DATA**

# 8WH2020-0AG00 SIEMENS Two-tier terminals with spring-loaded connection, Cross-section: 0.5-4 mm<sup>2</sup>, Width: 6.2..

Brand: SIEMENS | Manufacturer Part Number: 8WH2020-0AG00



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | SIEMENS                     |
| MPN / Reference | 8WH2020-0AG00               |
| Catalog number  | 20200                       |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-B80D40F997               |
| Generated       | 2026-08-02                  |

## Product Overview

Two-tier terminals with spring-loaded connection, Cross-section: 0.5-4 mm<sup>2</sup>, Width: 6.2mm, Color: gray  
Spring connection two-storey terminal, section: 0.5 - 4 mm<sup>2</sup>, width: 6.2 mm, colour: grey ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancellations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

Two-tier terminals with spring-loaded connection, Cross-section: 0.5-4 mm<sup>2</sup>, Width: 6.2mm, Color: gray

**Model**

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

**General technical data**

terminal contact spacing 6 mm

operating voltage / rated value 500 V

**Protection class**

combustibility class according to UL 94 V0

**Main circuit**

operational current / rated value 32 A

**Appearance**

color grey

**Product details**

product component / required / end cover plate No

**Number**

number of terminal levels 2

number of terminal points / per terminal level 2

**Connections**

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 6 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 6 mm<sup>2</sup>? maximum 6 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 4 mm<sup>2</sup>? with core end processing / maximum 4 mm<sup>2</sup>? without core end processing / minimum 4 mm<sup>2</sup>? without core end processing / maximum 4 mm<sup>2</sup>

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

**Mechanical Design**

height / with lowest-profile installation 47.5 mm

length 84 mm

fastening method DIN rail 35 mm

net weight 17 g

material / of the insulating body Other

**Environmental conditions**

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2020-0AG00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.