

INDUSTRIAL COMPONENT DATA

8WH2020-0CE07 SIEMENS Two-tier PE terminal with spring-loaded connection, Cross-section: 0.14-1.5 mm², Width..

Brand: SIEMENS | Manufacturer Part Number: 8WH2020-0CE07



Manufacturer	SIEMENS
MPN / Reference	8WH2020-0CE07
Catalog number	20200
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-0DCDB4DC8F
Generated	2026-08-01

Product Overview

Two-tier PE terminal with spring-loaded connection, Cross-section: 0.14-1.5 mm², Width: 4.2mm, Color: green-yellow
Spring connection two-story earth terminal, section: 0.14 - 1.5 mm², width: 4.2 mm, color: green-yellow (** ATTENTION :
Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Two-tier PE terminal with spring-loaded connection, Cross-section: 0.14-1.5 mm², Width: 4.2mm, Color: green-yellow
Model

product brand name ALPHA

product designation PE through-type terminal

General technical data

insulation material thermoplastic

terminal contact spacing 4.2 mm

Protection class

combustibility class according to UL 94 V0

Appearance

color green-yellow

Product details

product feature / PEN function No

product component / required / end cover plate No

Number

number of terminal levels 2

number of terminal points / per terminal level 2

Connections

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 0.14 mm²

? maximum 1.5 mm²

connectable conductor cross-section / stranded

? minimum 0.14 mm²

? maximum 1.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.14 mm²

? with core end processing / maximum 1.5 mm²

? without core end processing / minimum 1.5 mm²

? without core end processing / maximum 1.5 mm²

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 47.5 mm

length 67.5 mm

fastening method DIN rail 35 mm

net weight 13 g

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 35 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Furt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2020-0CE07 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.