


**INDUSTRIAL COMPONENT DATA**

# 8WH2035-0AF00 SIEMENS Three-tier terminal 2.5 mm2 with 1 potential for the 3L gray Width 5.2 mm

Brand: SIEMENS | Manufacturer Part Number: 8WH2035-0AF00



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 8WH2035-0AF00                           |
| Catalog number  | 20350                                   |
| Category        | Multi level installation terminal block |
| Minimum order   | 50 Pcs                                  |
| Document ID     | EO-F4080111F8                           |
| Generated       | 2026-08-02                              |

## Product Overview

Three-tier terminal 2.5 mm2; with 1 potential for the 3L; gray; Width 5.2 mm  
THREE-STORY TERMINAL 2.5 MM2; WITH 1 POTENTIAL FOR 3L; GREY; WIDTH 5.2 MM ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

Three-tier terminal 2.5 mm2; with 1 potential for the 3L; gray; Width 5.2 mm

**Model**

product brand name ALPHA

design of terminal / terminal levels internally linked No

**General technical data**

terminal contact spacing 5.2 mm

operating voltage / rated value 500 V

**Protection class**

combustibility class according to UL 94 V0

**Main circuit**

operational current / rated value 24 A

**Appearance**

color grey

Product details

product component / required / end cover plate No  
Number

number of terminal levels 3

number of terminal points / per terminal level 2

Connections

connectable conductor cross-section / solid

? minimum 0.08 mm<sup>2</sup>

? maximum 4 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 0.08 mm<sup>2</sup>

? maximum 2.5 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.25 mm<sup>2</sup>

? with core end processing / maximum 2.5 mm<sup>2</sup>

? without core end processing / minimum 0.08 mm<sup>2</sup>

? without core end processing / maximum 2.5 mm<sup>2</sup>

type of connection

? 1 spring-loaded terminal

? 2 spring-loaded terminal

position / of the terminal top

Mechanical Design

height 99.5 mm

height / with lowest-profile installation 58 mm

depth 58 mm

length 99.5 mm

fastening method DIN rail 35 mm

net weight 20 g

material / of the insulating body Other

Environmental conditions

ambient temperature / during operation

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and D...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH2035-0AF00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.