


## INDUSTRIAL COMPONENT DATA

# 8WH3000-0CE07 SIEMENS Protective conductor terminal with quick-connect technology Cross-section: 0.25-1.5 mm..

Brand: SIEMENS | Manufacturer Part Number: 8WH3000-0CE07



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | SIEMENS               |
| MPN / Reference | 8WH3000-0CE07         |
| Catalog number  | 30000                 |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-E2C65D3D60         |
| Generated       | 2026-08-02            |

## Product Overview

Protective conductor terminal with quick-connect technology Cross-section: 0.25-1.5 mm<sup>2</sup>, Width: 5.2mm, Color: green-yellow

Conex earth terminal. by insulation displacement, section: 0.25 - 1.5 mm<sup>2</sup>, width: 5.2 mm, color: green-yellow ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancelations and returns limited. Consult conditions.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; Terminals

## Additional Product Information

## Technical data

Protective conductor terminal with quick-connect technology Cross-section: 0.25-1.5 mm<sup>2</sup>, Width: 5.2mm, Color: green-yellow

## Model

product brand name ALPHA

product designation PE through-type terminal

## General technical data

insulation material thermoplastic

terminal contact spacing 5.2 mm

## Protection class

combustibility class according to UL 94 V0

**Appearance**

color green-yellow

**Product details**

product feature / PEN function No

product component / required / end cover plate No

**Number**

number of terminal levels 1

number of terminal points / per terminal level 2

**Connections**

connectable conductor cross-section / solid

? minimum 0.25 mm<sup>2</sup>? maximum 1.5 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 0.25 mm<sup>2</sup>? maximum 1.5 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.25 mm<sup>2</sup>? with core end processing / maximum 1.5 mm<sup>2</sup>? without core end processing / minimum 1.5 mm<sup>2</sup>? without core end processing / maximum 1.5 mm<sup>2</sup>

type of connection

? 1 insulation piercing connection

? 2 insulation piercing connection

position / of the terminal top

**Mechanical Design**

height / with lowest-profile installation 39.3 mm

length 58.8 mm

fastening method DIN rail 35 mm

net weight 11 g

material / of the insulating body Thermoplastic

**Environmental conditions**

ambient temperature / during operation

? minimum -25 °C

? maximum 35 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other

Confirmation

**Miscellaneous**

Fu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH3000-0CE07 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.