


INDUSTRIAL COMPONENT DATA

8WH3000-6AF00 SIEMENS Isolating terminal with quick-connect technology Cross-section: 0.5-2.5 mm2, Width: 6...

Brand: SIEMENS | Manufacturer Part Number: 8WH3000-6AF00



Manufacturer	SIEMENS
MPN / Reference	8WH3000-6AF00
Catalog number	30006
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-42F4A0A094
Generated	2026-08-01

Product Overview

Isolating terminal with quick-connect technology Cross-section: 0.5-2.5 mm2, Width: 6.2mm, Color: gray
Interruptible terminal with conex. by insulation displacement, section: 0.5-2.5 mm2, width: 6.2 mm, color: gray (**
ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancellations and returns limited.
Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Isolating terminal with quick-connect technology Cross-section: 0.5-2.5 mm2, Width: 6.2mm, Color: gray

Model

product brand name ALPHA

type of longitudinal separation others

type of lateral separation without

design of terminal / terminal levels internally linked No

General technical data

insulation material others

terminal contact spacing 6.2 mm

operating voltage / rated value 400 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 16 A

Appearance

color grey

Product details

product component

? required / end cover plate No

? test socket No

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

connectable conductor cross-section / solid

? minimum 2.5 mm²

? maximum 2.5 mm²

connectable conductor cross-section / stranded

? minimum 0.5 mm²

? maximum 2.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 2.5 mm²

? with core end processing / maximum 2.5 mm²

? without core end processing / minimum 2.5 mm²

? without core end processing / maximum 2.5 mm²

type of connection

? 1 insulation piercing connection

? 2 insulation piercing connection

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 42.8 mm

length 82.5 mm

fastening method DIN rail 35 mm

material / of the insulating body Other

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH3000-6AF00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.