

INDUSTRIAL COMPONENT DATA

8WH3004-0CE07 SIEMENS Protective conductor terminal with quick-connect technology 4 connection points, Cross..

Brand: SIEMENS | Manufacturer Part Number: 8WH3004-0CE07



Manufacturer	SIEMENS
MPN / Reference	8WH3004-0CE07
Catalog number	30040
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-07469625DD
Generated	2026-08-04

Product Overview

Protective conductor terminal with quick-connect technology 4 connection points, Cross-section: 0.25-1.5 mm², Width: 5.2mm, Color: green-yellow

Ground terminal with conex. by insulation displacement, 4 connection points, section: 0.25 - 1.5 mm², width: 5.2 mm, color: green-yellow (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Protective conductor terminal with quick-connect technology 4 connection points, Cross-section: 0.25-1.5 mm², Width: 5.2mm, Color: green-yellow

Model

product brand name ALPHA

product designation PE through-type terminal

General technical data

insulation material thermoplastic

terminal contact spacing 5.2 mm

Protection class

combustibility class according to UL 94 V0

Appearance

color green-yellow

Product details

product feature / PEN function No

product component / required / end cover plate No

Number

number of terminal levels 1

number of terminal points / per terminal level 4

Connections

connectable conductor cross-section / solid

? minimum 0.25 mm²? maximum 1.5 mm²

connectable conductor cross-section / stranded

? minimum 0.25 mm²? maximum 1.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.25 mm²? with core end processing / maximum 1.5 mm²? without core end processing / minimum 1.5 mm²? without core end processing / maximum 1.5 mm²

type of connection

? 1 insulation piercing connection

? 2 insulation piercing connection

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 39.3 mm

length 94 mm

fastening method DIN rail 35 mm

net weight 17 g

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 35 °C

Downloads and manualsGeneral Product Approval Declaration of Conformity other
Confirmati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH3004-0CE07 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.