

**INDUSTRIAL COMPONENT DATA**

# 8WH5000-0CF07 SIEMENS PE terminal, plug-in connection at both ends, Cross-section 0.08-2.5 mm<sup>2</sup>, Width: 5.2mm..

Brand: SIEMENS | Manufacturer Part Number: 8WH5000-0CF07



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | SIEMENS               |
| MPN / Reference | 8WH5000-0CF07         |
| Catalog number  | 50000                 |
| Category        | Ground terminal block |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-E6BE696FA6         |
| Generated       | 2026-08-01            |

## Product Overview

PE terminal, plug-in connection at both ends, Cross-section 0.08-2.5 mm<sup>2</sup>, Width: 5.2mm, Color: green-yellow  
 Plug-in ground terminal on both sides, section 0.08 - 2.5 mm<sup>2</sup>, width: 5.2 mm, color: green-yellow ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

PE terminal, plug-in connection at both ends, Cross-section 0.08-2.5 mm<sup>2</sup>, Width: 5.2mm, Color: green-yellow

**Model**

product brand name ALPHA

product designation PE through-type terminal

**General technical data**

insulation material thermoplastic

terminal contact spacing 5.2 mm

**Protection class**

combustibility class according to UL 94 V0

**Appearance**

color green-yellow

**Product details**

product feature / PEN function No  
product component / required / end cover plate No  
Number  
number of terminal levels 1  
number of terminal points / per terminal level 2  
Connections  
connectable conductor cross-section / solid  
? minimum 0.25 mm<sup>2</sup>  
? maximum 2.5 mm<sup>2</sup>  
connectable conductor cross-section / stranded  
? minimum 0.25 mm<sup>2</sup>  
? maximum 2.5 mm<sup>2</sup>  
connectable conductor cross-section / finely stranded  
? with core end processing / minimum 0.25 mm<sup>2</sup>  
? with core end processing / maximum 2.5 mm<sup>2</sup>  
? without core end processing / minimum 2.5 mm<sup>2</sup>  
? without core end processing / maximum 2.5 mm<sup>2</sup>  
type of connection  
? 1 connector  
? 2 connector  
position / of the terminal top  
Mechanical Design  
height / with lowest-profile installation 36.5 mm  
length 48.5 mm  
fastening method DIN rail 35 mm  
net weight 7 g  
material / of the insulating body Thermoplastic  
Environmental conditions  
ambient temperature / during operation  
? minimum -25 °C  
? maximum 35 °C  
Downloads and manuals  
General Product Approval Declaration of Conformity other  
Confirmation  
Miscellaneous  
Further information  
Information- and Downloadcenter (Catalog...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH5000-0CF07 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.