

INDUSTRIAL COMPONENT DATA

8WH6000-0AG00 SIEMENS Through-type terminals 4 mm², 6.2 mm wide gray

Brand: SIEMENS | Manufacturer Part Number: 8WH6000-0AG00



Manufacturer	SIEMENS
MPN / Reference	8WH6000-0AG00
Catalog number	60000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-8B4E1A0C47
Generated	2026-08-02

Product Overview

Through-type terminals 4 mm², 6.2 mm wide gray

STEP TERMINAL 4 MM², 6.2 MM WIDE GREY (** ATTENTION : Price per 1 Unit and Minimum Quantity / Multipurpose Order 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Through-type terminals 4 mm², 6.2 mm wide gray

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 6 mm

operating voltage / rated value 800 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 32 A

Appearance

color grey

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 12 mm

connectable conductor cross-section / solid

? minimum 0.2 mm²? maximum 6 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.3 mm²? with core end processing / maximum 4 mm²? without core end processing / minimum 0.2 mm²? without core end processing / maximum 4 mm²

type of connection

? 1 plug terminal connection

? 2 plug terminal connection

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 36.5 mm

length 56 mm

fastening method DIN rail 35 mm

net weight 9 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage...>**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 8WH6000-0AG00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.