

INDUSTRIAL COMPONENT DATA

8WH6000-0AK00 SIEMENS Through-type terminal 16 mm² IPO connection Terminal width 12 mm gray

Brand: SIEMENS | Manufacturer Part Number: 8WH6000-0AK00



Manufacturer	SIEMENS
MPN / Reference	8WH6000-0AK00
Catalog number	60000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-F683CF3E5E
Generated	2026-08-02

Product Overview

Through-type terminal 16 mm² IPO connection Terminal width 12 mm gray

Terminala de paso 16MM² technology IPO width 12MM gray (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals

Additional Product Information

Technical data

Through-type terminal 16 mm² IPO connection Terminal width 12 mm gray

Model

product brand name SENTRON

product designation ALPHA FIX terminal blocks

General technical data

terminal contact spacing 12 mm

operating voltage / rated value 1 000 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 90 A

Appearance

color grey

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 18 mm

connectable conductor cross-section / solid

? minimum 0.5 mm²

? maximum 25 mm²

connectable conductor cross-section / stranded

? minimum 0.5 mm²

? maximum 16 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.5 mm²

? with core end processing / maximum 16 mm²

? without core end processing / minimum 0.5 mm²

? without core end processing / maximum 16 mm²

type of connection

? 1 plug terminal connection

? 2 plug terminal connection

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 60.1 mm

length 75 mm

fastening method DIN rail 35 mm

net weight 37 g

material / of the insulating body Thermoplast

Environmental conditions

ambient temperature / during operation

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

Miscellaneous

Further information

Information- and Downloadcenter (C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH6000-0AK00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.