

INDUSTRIAL COMPONENT DATA

8WH6000-0CH07 SIEMENS PE terminal IPO technology, 6 mm2 Width 8.2 mm, yellow-green 2 closing points

Brand: SIEMENS | Manufacturer Part Number: 8WH6000-0CH07



Manufacturer	SIEMENS
MPN / Reference	8WH6000-0CH07
Catalog number	60000
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-82D6C3C1A8
Generated	2026-08-06

Product Overview

PE terminal IPO technology, 6 mm2 Width 8.2 mm, yellow-green 2 closing points

SPRING PE TERMINAL "IPO TECHNOLOGY", 6MM2 WIDE 8.2MM, GREEN-YELLOW 2 CONNECTION POINTS (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

PE terminal IPO technology, 6 mm2 Width 8.2 mm, yellow-green 2 closing points

Model

product brand name SENTRON

General technical data

terminal contact spacing 8 mm

Protection class

combustibility class according to UL 94 V0

Appearance

color green-yellow

Product details

product component / required / end cover plate Yes

Number

number of terminal levels 1

number of terminal points / per terminal level 2

Connections

stripped length 12 mm

connectable conductor cross-section / solid

? minimum 0.5 mm²? maximum 10 mm²

connectable conductor cross-section / stranded

? minimum 0.5 mm²? maximum 6 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.5 mm²? with core end processing / maximum 6 mm²? without core end processing / maximum 6 mm²

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 43.5 mm

length 58 mm

fastening method DIN rail 35 mm

net weight 22 g

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation**Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH6000-0CH07>

Service&Support (Manuals, Certificates, Characteri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH6000-0CH07 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.