

**INDUSTRIAL COMPONENT DATA**

# 8WH6000-0CJ07 SIEMENS PE terminal IPO technology, 6 mm2 Width 10.2 mm, yellow-green 2 closing points

Brand: SIEMENS | Manufacturer Part Number: 8WH6000-0CJ07



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | SIEMENS                     |
| MPN / Reference | 8WH6000-0CJ07               |
| Catalog number  | 60000                       |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-F71A1224C8               |
| Generated       | 2026-08-05                  |

## Product Overview

PE terminal IPO technology, 6 mm2 Width 10.2 mm, yellow-green 2 closing points

SPRING PE TERMINAL "IPO TECHNOLOGY", 10MM2 WIDE 8.2MM, GREEN-YELLOW 2 CONNECTION POINTS ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units \*\* ). Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

**Technical data**

PE terminal IPO technology, 6 mm2 Width 10.2 mm, yellow-green 2 closing points

**Model**

product brand name SENTRON

**General technical data**

terminal contact spacing 10 mm

**Protection class**

combustibility class according to UL 94 V0

**Appearance**

color green-yellow

**Product details**

product component / required / end cover plate Yes

**Number**

number of terminal levels 1

number of terminal points / per terminal level 2

**Connections**

stripped length 18 mm

connectable conductor cross-section / solid

? minimum 0.5 mm<sup>2</sup>? maximum 16 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 0.5 mm<sup>2</sup>? maximum 10 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.5 mm<sup>2</sup>? with core end processing / maximum 10 mm<sup>2</sup>? without core end processing / maximum 10 mm<sup>2</sup>

position / of the terminal top

**Mechanical Design**

height / with lowest-profile installation 49.5 mm

length 68 mm

fastening method DIN rail 35 mm

net weight 36 g

material / of the insulating body Thermoplastic

**Environmental conditions**

ambient temperature / during operation

? minimum -25 °C

? maximum 55 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation****Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH6000-0CJ07>

Service&amp;Support (Manuals, Certificates, Chara...)

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 8WH6000-0CJ07 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.