

INDUSTRIAL COMPONENT DATA

8WH6001-4MF00 SIEMENS Installation terminal 2.5 mm2, 5.2 mm width gray PE, L, L disconnect

Brand: SIEMENS | Manufacturer Part Number: 8WH6001-4MF00



Manufacturer	SIEMENS
MPN / Reference	8WH6001-4MF00
Catalog number	60014
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-6231D60D2F
Generated	2026-08-04

Product Overview

Installation terminal 2.5 mm2, 5.2 mm width gray PE, L, L disconnect

TERMINAL OF PASSAGE INSTAL PE,L,L-DISCON 2,5 MM2, 5,2 MM WIDTH GREY DISCONNECTION (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 50 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals
--------------	---

Additional Product Information

Technical data

Installation terminal 2.5 mm2, 5.2 mm width gray PE, L, L disconnect

Model

product brand name ALPHA

General technical data

insulation material thermoplastic

terminal contact spacing 5.2 mm

operating voltage / rated value 400 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 24 A

Appearance

color / of the insulating body gray

Product details

? product function / N function No

? product feature / N separation slides No

? product function / PE function Yes

product component

? required / end cover plate Yes

? test separator Yes

Number

number of potentials 3

Connections

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 0.25 mm²

? maximum 4 mm²

connectable conductor cross-section / stranded

? minimum 0.25 mm²

? maximum 2.5 mm²

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.25 mm²

? with core end processing / maximum 2.5 mm²

? without core end processing / minimum 0.25 mm²

? without core end processing / maximum 2.5 mm²

type of connection

? 1 plug terminal connection

? 2 plug terminal connection

position / of the terminal top

Mechanical Design

height / with lowest-profile installation 50.5 mm

length 101 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplastic

Environmental conditions

ambient temperature / during operation

? maximum 55 °C

Downloads and manuals

General Product Approval Declaration of Conformity oth...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 8WH6001-4MF00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.