

**INDUSTRIAL COMPONENT DATA**

# 8WH6020-0AF01 SIEMENS IPO terminals, Two-tier terminals

Brand: SIEMENS | Manufacturer Part Number: 8WH6020-0AF01



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 8WH6020-0AF01                           |
| Catalog number  | 60200                                   |
| Category        | Multi level installation terminal block |
| Minimum order   | 50 Pcs                                  |
| Document ID     | EO-8391B63E1B                           |
| Generated       | 2026-08-04                              |

## Product Overview

IPO terminals, Two-tier terminals

TERMINAL TERMINAL TERMINAL 2.5 MM2 WIDTH 5.2 MM COLOUR BLUE 4 ANCHOR POINTS ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Multipurpose Order 50 Units \*\* ). Cancelations and returns limited. Consult conditions.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > Terminals**

## Additional Product Information

Technical data

IPO terminals, Two-tier terminals

Model

product brand name ALPHA

design of terminal / terminal levels internally linked No

General technical data

terminal contact spacing 5.2 mm

operating voltage / rated value 500 V

Protection class

combustibility class according to UL 94 V0

Main circuit

operational current / rated value 26 A

Appearance

color blue

**Product details**

product component / required / end cover plate Yes

Number

number of terminal levels 2

number of terminal points / per terminal level 2

**Connections**

stripped length 10 mm

connectable conductor cross-section / solid

? minimum 0.14 mm<sup>2</sup>? maximum 4 mm<sup>2</sup>

connectable conductor cross-section / stranded

? minimum 0.14 mm<sup>2</sup>? maximum 2.5 mm<sup>2</sup>

connectable conductor cross-section / finely stranded

? with core end processing / minimum 0.14 mm<sup>2</sup>? with core end processing / maximum 2.5 mm<sup>2</sup>? without core end processing / minimum 2.5 mm<sup>2</sup>? without core end processing / maximum 2.5 mm<sup>2</sup>

position / of the terminal top

**Mechanical Design**

height 68 mm

height / with lowest-profile installation 47.5 mm

depth 55 mm

length 68 mm

fastening method DIN rail 35 mm

material / of the insulating body Thermoplast

**Environmental conditions**

ambient temperature / during operation

? maximum 55 °C

**Downloads and manuals**

General Product Approval Declaration of Conformity other

**Confirmation****Miscellaneous****Further information**Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online orde...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send SIEMENS / 8WH6020-0AF01 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](http://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.