

INDUSTRIAL COMPONENT DATA

LZS:PT78742 SIEMENS Plug-in socket for PT relay 4 changeover contacts with logic isolation screw terminal

Brand: SIEMENS | Manufacturer Part Number: LZS:PT78742



Manufacturer	SIEMENS
MPN / Reference	LZS:PT78742
Catalog number	78742
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-1DA08ED40B
Generated	2026-08-05

Product Overview

Plug-in socket for PT relay 4 changeover contacts with logic isolation screw terminal
SIRIUS Plug-in relays, accessory, socket for mounting, 4 CO, with logical separation, screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

Plug-in socket for PT relay 4 changeover contacts with logic isolation screw terminal

General technical data

display version LED No

protection class IP IP20

switching behavior monostable

design of the switching function changeover switch

design of the switching function positively driven No

reference code according to IEC 81346-2 U

Substance Prohibitance (Date) 05/01/2012

design of the relay operating mechanism poled

product component plug-in socket Yes

design of the snap-on socket base Socket with logic isolation

Auxiliary circuit

number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 0
number of CO contacts for auxiliary contacts 0
Connections/ Terminals
product function removable terminal No
type of electrical connection screw-type terminals
type of connectable conductor cross-sections
? solid 1x (1,0 ... 2,5), 2x 1,0, 2x 1,5, 2x 2,5
? finely stranded with core end processing 1x (1.0 ... 1.5), 2x 1.0, 2x 1.5
? at AWG cables solid 1x (18 ... 14), 2x 18, 2x 16, 2x 14
connectable conductor cross-section
? solid 1 ... 2.5 mm²
? finely stranded with core end processing 1 ... 1.5 mm²
AWG number as coded connectable conductor cross section
? solid 18 ... 14
tightening torque with screw-type terminals 0.5 ... 0.7 N·m
Installation/ mounting/ dimensions
mounting position any
fastening method snap-on mounting
height 77 mm
width 27 mm
depth 61 mm
Ambient conditions
ambient temperature
? during operation -40 ... +70 °C
? during stora...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / LZS:PT78742 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.