

INDUSTRIAL COMPONENT DATA

LZS:RT4D4L24 SIEMENS Plug-in relay complete unit 2 W, 24 V DC LED module red Socket with logic isolation Spr..

Brand: SIEMENS | Manufacturer Part Number: LZS:RT4D4L24



Manufacturer	SIEMENS
MPN / Reference	LZS:RT4D4L24
Catalog number	10000
Category	Switching relay
Minimum order	5 Pcs
Document ID	EO-F75CBBB997
Generated	2026-08-03

Product Overview

Plug-in relay complete unit 2 W, 24 V DC LED module red Socket with logic isolation Spring-type terminal (push-in)
'SIRIUS Plug-in relays, complete element, 24V DC, 2 CO, logic separation, spring connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

Plug-in relay complete unit 2 W, 24 V DC LED module red Socket with logic isolation Spring-type terminal (push-in)

product brand name SIRIUS

product designation Coupling relay with plug-in relay

product type designation LZS

General technical data

display version LED Yes

consumed active power 0.4 W

percental drop-out voltage related to the input voltage 10 %

protection class IP IP20

operating frequency without load 36 000 1/h

operating frequency with load 360 1/h

switching behavior monostable

design of the switching function changeover switch

design of the switching function positively driven No
mechanical service life (switching cycles) typical 30 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000
thermal current 8 A
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 05/01/2012
Control circuit/ Control
control supply voltage at DC
? rated value 24 V
operating range factor control supply voltage rated value at DC
? initial value 0.9
? full-scale value 1.4
closing delay
? at DC 8 ms
opening delay
? at DC 6 ms
design of the relay operating mechanism poled
product component plug-in socket Yes
design of the snap-on socket base Socket with logic isolation
Short-circuit protection
design of the fuse link for short-circuit protection of the auxiliary switch required fuse gG: 10 A
Auxiliary circuit
type of switching contact Changeover contact
material of switching contacts AgNi 90/10
number of NC contacts for auxiliar...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / LZS:RT4D4L24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.