

**INDUSTRIAL COMPONENT DATA**

# LZX:MT323024 SIEMENS Plug-in relay, 3 changeover contacts Relay with LED 28 mm, 24 V DC

Brand: SIEMENS | Manufacturer Part Number: LZX:MT323024



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | SIEMENS         |
| MPN / Reference | LZX:MT323024    |
| Catalog number  | 323024          |
| Category        | Switching relay |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-2F989A92F4   |
| Generated       | 2026-08-06      |

## Product Overview

Plug-in relay, 3 changeover contacts Relay with LED 28 mm, 24 V DC

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Function relays**

## Additional Product Information

**Technical data**

Plug-in relay, 3 changeover contacts Relay with LED 28 mm, 24 V DC

product brand name SIRIUS

product designation Plug-in relay

product type designation LZX

**General technical data**

consumed active power 1 200 mW

percental drop-out voltage related to the input voltage 10 %

shock resistance according to IEC 60068-2-27 10g / 11 ms

vibration resistance according to IEC 60068-2-6 30 ... 150 Hz: 2g

operating frequency without load 6 000 1/h

operating frequency with load 1 200 1/h

switching behavior monostable

design of the switching function changeover switch

design of the switching function positively driven No

mechanical service life (switching cycles) typical 20 000 000  
electrical endurance (switching cycles) at AC-15 at 230 V typical 300 000  
thermal current 10 A  
reference code according to IEC 81346-2 K  
Substance Prohibitance (Date) 05/01/2012  
Control circuit/ Control  
control supply voltage at DC  
? rated value 24 V  
operating range factor control supply voltage rated value at DC  
? initial value 0.9  
? full-scale value 1.4  
design of the relay operating mechanism poled  
product component plug-in socket No  
Auxiliary circuit  
type of switching contact Changeover contact  
material of switching contacts AgNi 90/10  
number of NC contacts for auxiliary contacts 0  
number of NO contacts for auxiliary contacts 0  
number of CO contacts for auxiliary contacts 3  
Main circuit  
type of voltage DC  
Connections/ Terminals  
product function removable terminal No  
Installation/ mounting/ dimens...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / LZXM:MT323024 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.