

INDUSTRIAL COMPONENT DATA

LZX:MT328230 SIEMENS Plug-in relay, 3 changeover contacts Relay with LED 38 mm, 230 V AC

Brand: SIEMENS | Manufacturer Part Number: LZX:MT328230



Manufacturer	SIEMENS
MPN / Reference	LZX:MT328230
Catalog number	328230
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-F9451BB7FF
Generated	2026-08-06

Product Overview

Plug-in relay, 3 changeover contacts Relay with LED 38 mm, 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Function relays**

Additional Product Information

Technical data

Plug-in relay, 3 changeover contacts Relay with LED 38 mm, 230 V AC

product brand name SIRIUS

product designation Plug-in relay

product type designation LZX

General technical data

percental drop-out voltage related to the input voltage 30 %

shock resistance according to IEC 60068-2-27 10g / 11 ms

vibration resistance according to IEC 60068-2-6 30 ... 150 Hz: 2g

operating frequency without load 6 000 1/h

operating frequency with load 1 200 1/h

switching behavior monostable

design of the switching function changeover switch

design of the switching function positively driven No

mechanical service life (switching cycles) typical 20 000 000

thermal current 10 A
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 05/01/2012
Control circuit/ Control
control supply voltage at AC
? at 50 Hz rated value 230 V
? at 60 Hz rated value 230 V
control supply voltage frequency
? 1 rated value 50 Hz
? 2 rated value 60 Hz
supply voltage frequency for auxiliary and control circuit rated value 50 ... 60 Hz
operating range factor control supply voltage rated value at AC at 50 Hz
? initial value 0.9
? full-scale value 1.1
operating range factor control supply voltage rated value at AC at 60 Hz
? initial value 0.9
? full-scale value 1.1
design of the relay operating mechanism poled
product component plug-in socket No
Auxiliary circuit
type of switching contact Changeover contact
material of switching contacts AgNi 90/10
number of NC contacts for auxiliary contacts...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / LZX:MT328230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.