

INDUSTRIAL COMPONENT DATA

LZX:PT270024 SIEMENS Plug-in relay, 2 change-over contacts 24 V DC, also for LZS sockets

Brand: SIEMENS | Manufacturer Part Number: LZX:PT270024



Manufacturer	SIEMENS
MPN / Reference	LZX:PT270024
Catalog number	270024
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-B18BDEB763
Generated	2026-08-05

Product Overview

Plug-in relay, 2 change-over contacts 24 V DC, also for LZS sockets

SIRIUS Plug-in relays, relay, 2CO, 24V DC.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Function relays**

Additional Product Information

Technical data

Plug-in relay, 2 change-over contacts 24 V DC, also for LZS sockets

product brand name SIRIUS

product designation Plug-in relay

product type designation LZX

General technical data

consumed active power 741 mW

percental drop-out voltage related to the input voltage 10 %

shock resistance according to IEC 60068-2-27 5g / 11 ms

vibration resistance according to IEC 60068-2-6 30 ... 150 Hz: 4g

operating frequency without load 36 000 1/h

operating frequency with load 360 1/h

switching behavior monostable

design of the switching function changeover switch

design of the switching function positively driven No
mechanical service life (switching cycles) typical 30 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 180 000
thermal current 12 A
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 05/01/2012
Control circuit/ Control
control supply voltage at DC
? rated value 24 V
operating range factor control supply voltage rated value at DC
? initial value 0.9
? full-scale value 1.4
design of the relay operating mechanism poled
product component plug-in socket No
Auxiliary circuit
type of switching contact Changeover contact
material of switching contacts AgNi 90/10
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 0
number of CO contacts for auxiliary contacts 2
operational current of auxiliary contacts at AC-15
? at 250 V 4 A
operational current at DC-13 at 24 V rated value 4 A
operatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / LZX:PT270024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.