

INDUSTRIAL COMPONENT DATA

CFX 10X40X1 CFX1185 TEKNOMEGA INSULATED COPPER FLEXIBLE BARS CO-FLEX 10X40X1 LENGTH 2MT

Brand: TEKNOMEGA | Manufacturer Part Number: CFX 10X40X1



Manufacturer	TEKNOMEGA
MPN / Reference	CFX 10X40X1
Catalog number	CFX1185
Category	Busbar
Minimum order	2 Pcs
Document ID	EO-FA10E3CC66
Generated	2026-08-05

Product Overview

INSULATED COPPER FLEXIBLE BARS CO-FLEX 10X40X1 LENGTH 2MT

PLETINA AISLADA FLEXIBLE CO-FLEX 10X40X1

COFLEX - Insulated copper flexible bars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	TEKNOMEGA
--------------	-----------

Additional Product Information

Technical Characteristics

Conductor

Electrolytic copper:

Cu-ETP - EN 13599

Laminate thickness:

0,5 - 0,8 - 1mm

Insulation

PVC compound

Black color with a white line

Self-extinguishing: UL 94-V0

Thickness: 2 mm

Dielectric rigidity: 20 kV/mm

Class II according to Par. 8.4.4 IEC 61439-1

Recyclable

Finishinged product

Rated voltage:

1000V AC / 1500V DC

Working temperature: -40 °C ÷ +105 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send TEKNOMEGA / CFX 10X40X1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.