

INDUSTRIAL COMPONENT DATA

CFP 3X40X1 CFX5160 TEKNOMEGA INSULATED COPPER FLEXIBLE BARS CO-FLEX PLUS 3X40X1 LENGTH 2MT

Brand: TEKNOMEGA | Manufacturer Part Number: CFP 3X40X1



Manufacturer	TEKNOMEGA
MPN / Reference	CFP 3X40X1
Catalog number	CFX5160
Category	Busbar
Minimum order	4 Pcs
Document ID	EO-559842AD18
Generated	2026-08-04

Product Overview

INSULATED COPPER FLEXIBLE BARS CO-FLEX PLUS 3X40X1 LENGTH 2MT

PLETINA AISLADA FLEXIBLE CO-FLEX PLUS 3X40X1

COFLEX PLUS - Insulated copper flexible bars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	TEKNOMEGA
--------------	-----------

Additional Product Information

Technical Characteristics

Conductor

Tinned electrolytic copper:

Cu-ETP - EN 13599

Laminate thickness:

0,5 - 0,8 - 1mm

Insulation

TPE compound

Black color with a light blue line

Low smoke emission

Self-extinguishing: UL 94-V0

Halogen free

Thickness: 1,9 mm

Dielectric strenght: 20 kV/mm
Class II according to Par. 8.4.4 IEC 61439-1
Recyclable
Finishinged product
Rated voltage:
1000V AC / 1500V DC
Working temperatures: ?-40 °C ÷ +140 °C?

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send TEKNOMEGA / CFP 3X40X1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.