

INDUSTRIAL COMPONENT DATA

CFP 4X40X1 CFX5165 TEKNOMEGA INSULATED COPPER FLEXIBLE BARS CO-FLEX PLUS 4X40X1 LENGTH 2MT

Brand: TEKNOMEGA | Manufacturer Part Number: CFP 4X40X1



Manufacturer	TEKNOMEGA
MPN / Reference	CFP 4X40X1
Catalog number	CFX5165
Category	Busbar
Minimum order	3 Pcs
Document ID	EO-A17653AE14
Generated	2026-08-04

Product Overview

INSULATED COPPER FLEXIBLE BARS CO-FLEX PLUS 4X40X1 LENGTH 2MT

PLETINA AISLADA FLEXIBLE CO-FLEX PLUS 4X40X1

COFLEX PLUS - Flexible copper insulated plates

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	TEKNOMEGA
--------------	-----------

Additional Product Information

Specifications

Driver

Tinned electrolytic copper:

Cu-ETP - EN 13599

Thickness of the blades:

0.5 - 0.8 - 1 mm

Isolation

TPE Compound

Black color with blue line.

Low smoke emission

Self-extinguishing: UL 94-V0

Halogen-free

Thickness: 1.9mm

Dielectric strength: 20 kV/mm

Class II according to Par. 8.4.4 IEC 61439-1

Recyclable

Finished product

Rated voltage:

1000 V AC / 1500 V DC

Working temperatures: $-40\text{ }^{\circ}\text{C} \div +140\text{ }^{\circ}\text{C}$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send TEKNOMEGA / CFP 4X40X1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.