

INDUSTRIAL COMPONENT DATA

NC50-S/25M 7TCA298000R0281 THOMAS AND BETTS NC SLIT HARNESSFLEX NYL NGR NW48 TUBE

Brand: THOMAS AND BETTS | Manufacturer Part Number: NC50-S/25M


Product image
not available

Manufacturer	THOMAS AND BETTS
MPN / Reference	NC50-S/25M
Catalog number	7TCA298000R0281
Category	Corrugated plastic hose
Minimum order	25 m.
Document ID	EO-4DD76FBB60
Generated	2026-08-03

Product Overview

NC SLIT HARNESSFLEX NYL NGR NW48 TUBE
50MM SLIT PA6 CONDUIT 25M - BL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > Harnessflex

Additional Product Information

Extended Product Type:NC50-S/25M

Product ID:7TCA298000R0281

EAN:5020963047718

Catalog Description:CONDUIT 50MM SLIT NYLON 25M COIL

Long Description:Standard Weight, General Purpose Slit Conduit, NC Size 50/NW Size 48, Outside Diameter 54.5mm,
Inside Diameter 46.9mm, Static Bend Radius 70mm, High Flexibility and Fatigue Life, IP40 Rating, Polyamide 6, Reel
Length 25 Meters, Black

Ordering

EAN:5020963047718

Dimensions

Product Net Depth / Length:25m

Product Net Weight:11.05lb

5.011 kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:40 in

1016 mm

Package Level 1 Height:50 in

1270 mm

Package Level 1 Depth / Length:48 in

1219 mm

Package Level 2 Units:5 piece

Package Level 2 Width:40 in

1016 mm

Package Level 2 Height:50 in

1270 mm

Package Level 2 Depth / Length:48 in

1219 mm

Package Level 3 Units:5 piece

Package Level 3 Width:40 in

1016 mm

Package Level 3 Height:50 in

1270 mm

Package Level 3 Depth / Length:48 in

1219 mm

Additional Information

Application:General Purpose

Brand / Label:Harnessflex

Color:Black

Flexibility:Very High

Inside Diameter:46.9 mm

Material:Polyamide/Nylon 6

Nominal Size:NC50/NW48

Number of Batteries:0

Outside Diameter:54.5 mm

Product Name:"flexible conduit, nylon"

Product Type:Slit Standard Weight Conduit

Radius:Static: 70 mm

Standards:ADR Approved, RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC

UPC:786210240985

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:NC50-S/25M

Declaration...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / NC50-S/25M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.