

INDUSTRIAL COMPONENT DATA

NENZ0405S/P5 7TCA297180R1010 THOMAS AND BETTS EXE NC20,M25 9-13 FITTING

Brand: THOMAS AND BETTS | Manufacturer Part Number: NENZ0405S/P5



Manufacturer	THOMAS AND BETTS
MPN / Reference	NENZ0405S/P5
Catalog number	7TCA297180R1010
Category	Screw connection for corrugated plastic hose
Minimum order	10 Pcs
Document ID	EO-9F40ADD2CD
Generated	2026-08-05

Product Overview

EXE NC20,M25 9-13 FITTING
EXE STRN RELIEF FTNG NC20,M25 9-13

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	THOMAS AND BETTS > PMA cable protection
--------------	---

Additional Product Information

Extended Product Type:NENZ0405S/P5

Product ID:7TCA297180R1010

EAN:5011949245563

Catalog Description:EXE STRN RELIEF FTNG NC20,M25 9-13

Long Description:Conduit Fitting with Strain Relief, Straight with External Male Thread, Conduit Size 20mm, M25 Thread, Minimum Bore 17mm, Suitable for Unbraided Nylon Conduit, Clamping Range 9.0 to 13.0 K, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black

Ordering

EAN:5011949245563

Dimensions

Product Net Weight:1lb

453.515 g

Container Information

Package Level 1 Units:10 piece

Package Level 1 Width:11.9 in
302 mm

Package Level 1 Height:7.9 in
201 mm

Package Level 1 Depth / Length:8.3 in
211 mm

Package Level 2 Units:80 piece

Package Level 2 Width:15.8 in
401 mm

Package Level 2 Height:11.9 in
302 mm

Package Level 2 Depth / Length:8.3 in
211 mm

Additional Information

Application:For Indoor and Outdoor Applications

Brand / Label:PMA

Color:Black

Insulation Class:IP68

Material:Modified Nylon 12 with Nickel Plated Threads

Number of Batteries:0

Product Name:NYLON EX FITTING

Product Type:Straight Conduit Fitting with Male Thread and Strain Relief

Size:Conduit Size 20mm ; M25 Thread

Special Functions:Nickel Plated Threads for Extra Stength

Standards:ATEX:SEV15ATATEX0121, IECEx:IECEx SEV15.0009, Ex eb IIC, Ex tb IIIC

Temperature Range:-20 to 85 °C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:9AKK106930A7766

Declaration of Conformity - CE:9AKK107680A0674

Instr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / NENZ0405S/P5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.