

INDUSTRIAL COMPONENT DATA

NENZ0808S/P2 7TCA297120R0379 THOMAS AND BETTS EXE STRAIGHT FITTING ROSC MALE M50 32-36

Brand: THOMAS AND BETTS | Manufacturer Part Number: NENZ0808S/P2



Manufacturer	THOMAS AND BETTS
MPN / Reference	NENZ0808S/P2
Catalog number	7TCA297120R0379
Category	Screw connection for corrugated plastic hose
Minimum order	10 Pcs
Document ID	EO-8B448A68C8
Generated	2026-08-05

Product Overview

EXE STRAIGHT FITTING ROSC MALE M50 32-36

EX STRN RELIEF FTNG NC50,M50 32-36

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > PMA cable protection

Additional Product Information

Extended Product Type:NENZ0808S/P2

Product ID:7TCA297120R0379

EAN:5011949240254

Catalog Description:EX STRN RELIEF FTNG NC50,M50 32-36

Long Description:Conduit Fitting with Strain Relief, Straight with External Male Thread, Conduit Size 50mm, M50 Thread, Minimum Bore 48mm, Suitable for Unbraided Nylon Conduit, Clamping Range 32.0 to 36.0 K, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black

Ordering

EAN:5011949240254

Dimensions

Product Net Weight:.1lb

45.351 g

Container Information

Package Level 1 Units:10 piece

Package Level 1 Width:11.9 in
302 mm

Package Level 1 Height:7.9 in
201 mm

Package Level 1 Depth / Length:8.3 in
211 mm

Package Level 2 Units:40 piece

Package Level 2 Width:15.8 in
401 mm

Package Level 2 Height:11.9 in
302 mm

Package Level 2 Depth / Length:8.3 in
211 mm

Additional Information

Application:For Indoor and Outdoor Applications

Brand / Label:PMA

Color:Black

Insulation Class:IP68

Material:Modified Nylon 12 with Nickel Plated Threads

Number of Batteries:0

Product Name:NYLON EX FITTING

Product Type:Straight Conduit Fitting with Male Thread and Strain Relief

Size:Conduit Size 50mm ; M50 Thread

Special Functions:Nickel Plated Threads for Extra Stength

Standards:ATEX:SEV15ATATEX0121, IECEx:IECEx SEV15.0009, Ex eb IIC, Ex tb IIIC

Temperature Range:-20 to 85 °C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:9AKK106930A7766

Declaration of Conformity - CE:9AKK107680A0674

Inst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / NENZ0808S/P2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.