

INDUSTRIAL COMPONENT DATA

TY225-50X 7TCG054360R0236 THOMAS AND BETTS CABLE TIE 50LB 9IN UV BLACK NYLON

Brand: THOMAS AND BETTS | Manufacturer Part Number: TY225-50X



Manufacturer	THOMAS AND BETTS
MPN / Reference	TY225-50X
Catalog number	7TCG054360R0236
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-43B770D9EA
Generated	2026-08-05

Product Overview

CABLE TIE 50LB 9IN UV BLACK NYLON
BRIDA TYFAST 226x4,6mm PA UV

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > Cable management flanges

Additional Product Information

Extended Product Type:TY225-50X

Product ID:7TCG054360R0236

EAN:5414363061397

Catalog Description:CABLE TIE 50LB 9IN UV BLACK NYLON

Long Description:Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 228mm, Width of 4.7mm, Thickness of 1.2mm , Tensile Strength Rating of 220 Newtons, 1000 Pack

Ordering

EAN:5414363061397

UPC:786210374390

Country of Origin:Hungary (HU)

Selling Unit of Measure:each

Dimensions

Product Net Width:0.19in

4.8 mm

Product Net Depth / Length:228mm

8.976 in

Container Information

Package Level 1 Units:1000 piece

Package Level 1 Width:1 in

25 mm

Package Level 1 Height:14 in

356 mm

Package Level 1 Depth / Length:18 in

457 mm

Package Level 2 Units:10000 piece

Package Level 2 Width:15.25 in

387 mm

Package Level 2 Height:11 in

279 mm

Package Level 2 Depth / Length:23.25 in

591 mm

Technical UL/CSA

Flammability According to UL94:V-2

Additional Information

Brand / Label:Ty-Fast

Bundle Diameter:57 mm

2.244 in

Color:Black

Effective Date:19970425

Lock Type:Plastic Pawl

Material:Nylon/Polyamide 6.6

Product Name:CATAMOUNT FASTENING PRODUCTS

Product Type:General Purpose

Special Functions:"The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / TY225-50X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.