

INDUSTRIAL COMPONENT DATA

TY244M 7TCG009130R0005 THOMAS AND BETTS CABLE TIE
30LB 14.5IN NAT NYLON

Brand: THOMAS AND BETTS | Manufacturer Part Number: TY244M



Manufacturer	THOMAS AND BETTS
MPN / Reference	TY244M
Catalog number	7TCG009130R0005
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-B6E1160382
Generated	2026-08-02

Product Overview

CABLE TIE 30LB 14.5IN NAT NYLON

TYRAP BLEND 368x3.6 NATURAL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > Cable management flanges

Additional Product Information

Extended Product Type:TY244M

Product ID:7TCG009130R0005

EAN:5414363062004

Catalog Description:CABLE TIE 30LB 14.5IN NAT NYLON

Long Description:Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 366mm (14.4 Inches), Width of 3.6mm (0.14 Inch), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 134 Newtons (30 Pounds), Bulk Pack

Ordering

E-Number (Finland):1381532

EAN:5414363062004

UPC:786210830728

Country of Origin:Hungary (HU)

Selling Unit of Measure:each

Dimensions

Product Net Width:0.14in

3.6 mm

Product Net Depth / Length:14.4in

366 mm

Container Information

Package Level 1 Units:1000 piece

Package Level 2 Units:10000 piece

Package Level 2 Width:15.9 in

404 mm

Package Level 2 Height:10.9 in

277 mm

Package Level 2 Depth / Length:23.1 in

587 mm

Technical UL/CSA

Flammability According to UL94:V-2

Additional Information

Brand / Label:Ty-Rap

Bundle Diameter:0.08 to 4.02 in

2 to 102 mm

Color:Natural

Effective Date:19710315

Lock Type:Stainless Steel Barb

Material:Nylon/Polyamide 6.6

Product Name:NYLON CABLE TIE

Product Type:High Performance

Special Functions:Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads.

Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.

Standards:UL E49405

Tensile Strength:30 lb

134 N

Thickness:0.04 in

1.0 mm

Certificates a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / TY244M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.