

INDUSTRIAL COMPONENT DATA

7TCG009130R0006 THOMAS AND BETTS CABLE TIE 40LB 14.5IN UV BLACK NYL

Brand: THOMAS AND BETTS | Manufacturer Part Number: TY244MX



Manufacturer	THOMAS AND BETTS
MPN / Reference	TY244MX
Catalog number	7TCG009130R0006
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-CB500792FD
Generated	2026-08-04

Product Overview

CABLE TIE 40LB 14.5IN UV BLACK NYL
BRIDA TYRAP 368x3,6 UV

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	THOMAS AND BETTS > Cable management flanges
--------------	---

Additional Product Information

Extended Product Type:TY244MX

Product ID:7TCG009130R0006

EAN:5414363062097

Catalog Description:CABLE TIE 40LB 14.5IN UV BLACK NYL

Long Description:Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 366mm (14.4 Inches), Width of 3.6mm (0.14 Inch), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 130 Newtons (29 pounds), Bulk Pack

Ordering

EAN:5414363062097

UPC:786210878010

Country of Origin:Hungary (HU)

Selling Unit of Measure:each

Dimensions

Product Net Width:0.14in

3.6 mm

Product Net Depth / Length:14.4in

366 mm

Container Information

Package Level 1 Units:1000 piece

Package Level 2 Units:10000 piece

Package Level 2 Width:17 in

432 mm

Package Level 2 Height:10.9 in

277 mm

Package Level 2 Depth / Length:23.3 in

592 mm

Technical UL/CSA

Flammability According to UL94:V-2

Additional Information

Brand / Label:Ty-Rap

Bundle Diameter:0.08 to 4.02 in

2 to 102 mm

Color:Black

Effective Date:19710315

Lock Type:Stainless Steel Barb

Material:Nylon/Polyamide 6.6

Product Name:CABLE TIE

Product Type:High Performance

Special Functions:Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads.

Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.

Standards:UL E49405

Tensile Strength:29 lb

130 N

Thickness:0.04 in

1.0 mm

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / TY244MX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.