

INDUSTRIAL COMPONENT DATA

**7TAG009130R0009 THOMAS AND BETTS CABLE TIE 30LB
5.5IN UV BLK NYLON**

Brand: THOMAS AND BETTS | Manufacturer Part Number: TY24MX



Manufacturer	THOMAS AND BETTS
MPN / Reference	TY24MX
Catalog number	7TAG009130R0009
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-E84AC059AE
Generated	2026-08-02

Product Overview

CABLE TIE 30LB 5.5IN UV BLK NYLON

BRIDA TYRAP 140x3,6 UV

CABLE TIE 5.5IN 40LB UV BLACK

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > Cable management flanges

Additional Product Information

Extended Product Type:TY24MX

Product ID:7TAG009130R0009

EAN:5414363062257

Catalog Description:CABLE TIE 5.5IN 40LB UV BLACK

Long Description:Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) Length of 139.7mm (5.5 Inches), Width of 3.6mm (0.14 Inches), Tensile Strength Rating of 178 Newtons (40 Pounds), Bulk Pack
Ordering

E-Number (Finland):1381509

EAN:5414363062257

UPC:786210826448

Country of Origin:Hungary (HU)

United States (US)

Japan (JP)

Selling Unit of Measure:each

Dimensions

Product Net Width:0.14in

3.6 mm

Product Net Depth / Length:5.5in

139.7 mm

Container Information

Package Level 1 Units:1000 piece

Package Level 1 Width:8.7 in

221 mm

Package Level 1 Height:2.7 in

69 mm

Package Level 1 Depth / Length:10.1 in

257 mm

Package Level 2 Units:10000 piece

Package Level 2 Width:10.9 in

277 mm

Package Level 2 Height:10.9 in

277 mm

Package Level 2 Depth / Length:13.2 in

335 mm

Technical UL/CSA

Flammability According to UL94:V-2

Additional Information

Brand / Label:Ty-Rap

Bundle Diameter:0.08 to 1.38 in

2 to 35 mm

Color:Black

Effective Date:19680112

Lock Type:Stainless Steel Barb

Product Name:PLASTIC CABLE TIE

Product Type:High Performance

Special Functions:Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads.

Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.

Standards:UL E49405

Tensile Strength:40 lb

178 N

Thickness:0.04 in

1.0 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / TY24MX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.