

INDUSTRIAL COMPONENT DATA

TY25MX-RW 7TCG009210R0085 THOMAS AND BETTS TY25MX FOR RAILWAY

Brand: THOMAS AND BETTS | Manufacturer Part Number: TY25MX-RW



Manufacturer	THOMAS AND BETTS
MPN / Reference	TY25MX-RW
Catalog number	7TCG009210R0085
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-E65D0E6A52
Generated	2026-08-02

Product Overview

TY25MX FOR RAILWAY
BRIDA TYRAP 186x4,8 RAIL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path THOMAS AND BETTS > Cable management flanges

Additional Product Information

Extended Product Type:TY25MX-RW

Product ID:7TCG009210R0085

EAN:5415022180176

Catalog Description:TY25MX FOR RAILWAY

Long Description:Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 185.67mm (7.31 Inches), Width of 4.9mm (0.19 Inches), Thickness of 1.09mm (0.043 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), 500 Bulk Pack

Ordering

EAN:5415022180176

UPC:786209716705

Country of Origin:Hungary (HU)

Selling Unit of Measure:each

Dimensions

Product Net Width:0.184in

4.67 mm

Product Net Depth / Length:7.2in

183 mm

Container Information

Package Level 1 Units:1000 piece

Package Level 1 Width:10.21 in

259 mm

Package Level 1 Height:1.96 in

50 mm

Package Level 1 Depth / Length:14.14 in

359 mm

Package Level 2 Units:10000 piece

Package Level 2 Width:14.7 in

373 mm

Package Level 2 Height:9.5 in

241 mm

Package Level 2 Depth / Length:21.2 in

538 mm

Technical UL/CSA

Flammability According to UL94:V-2

Additional Information

Brand / Label:Ty-Rap

Bundle Diameter:0.12 to 1.89 in

3 to 48 mm

Color:Black

Effective Date:20130730

Lock Type:Stainless Steel Barb

Material:Nylon/Polyamide 6.6

Product Name:OTHER ARTICLES OF PLASTIC

Product Type:High Performance

Special Functions:Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads.

Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send THOMAS AND BETTS / TY25MX-RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.